

JR_ALLE

14.01.2019

Actuator:

General Data

Type reference:	JR(M)(VA)(SW)(T)(TLR)(F)(FLR)(FT)(N)(R)(E)(WA)(WB)(WC)(WD)(STA)(STB)(SSAxxE)(L)
Description:	Rondex-Juwel Actuator (JR), without contact units, separate plungers
Approvals:	CE, UL
Degree of protection:	IP65 / IP67
Operation travel:	6 mm
Max. storage temperature:	-40°C ... 80°C
Max. operating temperature:	-25°C ... 70°C
Mechanical life:	see *1)
Electrical life (rated load):	see *2)

Additional Data

Mounting aperture:	22.3mm
Tightening torque (mounting nut):	1.5 ... 2.2 Nm
Panel thickness:	1.0 ...7.0 mm
Mounting position:	any
Standards:	EN 60947-5-1, EN 61058-1

Note

T...pushbutton head (charcoal), MT... pushbutton head (silver-coloured)
 F... pushbutton head (push-push/ charcoal), MF...pushbutton head (push-push/silver-coloured)
 TLR...pushbutton head with ring illumination (charcoal), MTLR...pushbutton head with ring illumination (silver-coloured)
 N...pilot light head (charcoal), MN...pilot light head (silver-coloured)
 SSA...key actuator(charcoal), MSSA...key actuator (silver-coloured)

STA(L), STB(L)...momentary selector head (charcoal), MSTA(L), MSTB(L)... momentary selector head (silver-coloured)

WA(L), WB(L)...maintained selector head (charcoal), MWA, MWB...maintained selector head (silver-coloured), (L)...illuminating option

WC(L), WD(L)...maintained selector head (charcoal), MWC, MWD...maintained selector head (silver-coloured), (L)...illuminating option

suitable for the following contact elements:
 MT..., ET..., DT..., DST...

*1,2) Lifetime Information

The mechanical and electrical lifetime depends on the actuator type (pushbutton, selector/ key-

operated type...) and on the type and number of contact elements used.