

SVACFT_ALLE

09.12.2016

Membrane pushbutton head, black



General Data

Type reference	S(VA)(SW)CFT(L)(X)(F)(P)(_)(YYYY)
Description	Single membrane pushbutton with integrated contact block, with Faston or PCB-mount terminals
Approvals	CE, cURus, DGUV_Test, DNV, ENEC10, VDE, UKCA
Contact type	1 inverter
Degree of protection	IP66 / IP67 / IP69K
Operation travel	1.8 mm
Connection type	Faston terminals 2.8 x 0.8 mm / PCB-mount terminals
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	1 million switching cycles (20°C)
Electrical life (rated load)	1 million switching cycles at rated load
Contact resistance NO	< 50 mOhm (new state)
Contact resistance NC	< 100 mOhm (new state)
Bouncing time NO	< 10ms
Bouncing time NC	< 10ms

Technical Data - Lamp

Lamp socket	none, with integrated 3 mm LED white
Max. lamp voltage	30 V AC/DC
Max. lamp output	14 mA (at 24 V DC)
Definition	X1...anode, X2...cathode

Additional data

Mounting aperture	22.3 mm
Tightening torque (mounting nut)	1.5 ... 1.9 Nm
Mounting position	any
Standards	EN 61058-1



Electrical features

Rated voltage 20 mV ... 48 V AC/DC

Rated current 0.01 mA ... 100 mA

Note

Kind of contact 1W=1 inverter

SVACFT(L)(X)(F)(P)(_) (YYYY) (!)...optional

(VA) = stainless steel front ring

(SW) = plastic front ring, black

(L) = illumination option

(X) = colour membrane ring, standard=black (W=white, R=red, Y=yellow, G=green, B=blue)

(F) = with Faston terminals 2.8x0.8 mm

(P) = with PCB-mount terminals

(YYYY) = labelling variants

Use in hygienic areas: variant with stainless steel front ring (VA)

- permanent in the range of -25°C to +40°C, for a short time up to +70°C

Data acc. to UL508

Rating 20mV...48 V AC/DC, 0.01mA...100 mA , max. 250 mW

