

Illuminated contact block, momentary CTLF

Category:	Contact blocks
Series:	Contact blocks C...F
Protection class:	II (protective insulation)
Degree of protection:	IP00
Switching function:	momentary action
Travel:	3 mm
Illumination:	yes
Contact equipment:	1 inverter
Connection type:	Faston terminals 2.8 x 0.8 mm
Mechanical life:	1 million switching cycles
Accessory type:	contact block
Operating temperature:	-30°C ... 70°C, without illumination -30°C ... 55°C, using incandescent lamps -30°C ... 65°C, using LEDs
Tactile:	yes
Electrical life:	1 million switching cycles at rated load
Storage temperature:	-50°C ... 85°C
Contact material:	gold-plated 1.5µm
Lamp socket:	T5,5K

Necessary accessory



Ultra-bright LED, T5,5K socket, 12V L5,5K12UW



Two-colour LED, T5,5K socket - 24V L5,5K24RG



Ultra-bright LED, T5,5K socket, 24V L5,5K24UB



Ultra-bright LED, T5,5K socket, 24V L5,5K24UG




Ultra-bright LED, T5,5K socket, 24V L5,5K24UR



Ultra-bright LED, T5,5K socket, 24V L5,5K24UW



Ultra-bright LED, T5,5K socket, 24V L5,5K24UY



Optional accessory



Plug-in socket with 5 contacts CAFP5



Double Faston FD2,8



Faston clamp 2.8 x 0.8 mm with snap-in pin FH2,8



Insulating case IH2,8



LED adapter LA5,5

