



DIRL2V-R16

06.05.2015

Insulated plastic enclosure, 2 mounting holes

3	٠	હ
2	٠	۲

General Data	
Type reference	DIRL2V-R16
Description	Enclosure
Approvals	CE, UKCA
Max. storage temperature	-40°C 70°C
Max. operating temperature	-25°C 60°C
Material	PA6

Technical data	
Mounting aperture	16 mm
Number of mounting holes	2
Cable entry	M20 x 1.5
Mounting depth	69 mm
Weight	approx. 266 g
Tightening torque (enclosure screws)	2.0 Nm

Note

Insulated Plastic Enclosure with anodised aluminium front plate (engraving, printing or laser marking on request) Picture may be different from original

Colour of bottom: dark-grey Colour of cover: light-grey


Georg Schlegel GmbH & Co. KG Kapellenweg 4 88525 Dürmentingen / Germany ↓ +49 (0)7371 / 502-0
➡ +49 (0)7371 / 502 49
@ info@schlegel.biz
www.schlegel.biz











Georg Schlegel GmbH & Co. KG Kapellenweg 4 88525 Dürmentingen / Germany +49 (0)7371 / 502-0
→49 (0)7371 / 502 49
@ info@schlegel.biz
www.schlegel.biz

