

### Emergency braking head with arrow DXRV39PF

Description:	must be mounted onto yellow background!
Category:	Emergency-stops
Series:	DUX-Basic
Panel cut-out:	Ø 22.3 mm
Degree of protection:	IP65
Switching function:	maintained action
Illumination:	no
With labelling option:	no
Front bezel	grey
mushroom head	red
Mechanical life:	300,000 switching cycles
Shape:	round
Permissive contact:	no
Anti-lock collar:	no
Switching position	yes
indicator:	
Release:	twist

### Optional accessory



Dummy module DB



Insulated plastic enclosure, 1 mounting hole D1RL1V-R22



Insulated plastic enclosure, 1 mounting hole D1RL1VGB-R22



Insulated plastic enclosure, 2 mounting holes D1RL2V-R22



Insulated plastic enclosure, 3 mounting holes D1RL3V-R22



Insulated plastic enclosure, 3 resp. 4 mounting holes D1RL4V-R22



Self-monitoring emergency contact block, momentary\*  
DMTOSFA



Modular contact block, momentary DSTI



Modular contact block, momentary DSTO



Modular contact block, momentary DTI



Modular contact block, momentary DTIV



Modular contact block, momentary DTO



Modular contact block, momentary DTON



Contact block, momentary ETR




Contact block, momentary ETR2



Insulated plastic enclosure, 1 mounting hole IRL1M



Insulated plastic enclosure, 1 mounting hole IRL1M\_GELB



Insulated plastic enclosure, 2 mounting holes IRL2M



Insulated plastic enclosure, 3 mounting holes IRL3M



Insulated plastic enclosure, 5 mounting holes IRL5M



Modular contact block, momentary MTI



Modular contact block, momentary MTIV



Modular contact block, momentary MTO



Modular contact block, momentary MTON



Yellow nameplate NAS\_22



Yellow nameplate with quadrilingual imprint NAS\_22\_548



Insulated plastic enclosure with 1 mounting hole SIL22/1



High insulated plastic enclosure with 1 mounting hole SILH22/1

