


**General Data**

Type Reference	IKEPTR
Description	Three-level wiring terminal
Approvals	CE, UKCA
Terminal type	Three-level wiring terminal, neutral wire terminal, feed-through terminal, earth terminal
Terminal width	6 mm
Mounting method	top hat rail N35, EN60715 TH35
Connection type	screw connection, slotted screw
Thread size of screw connection	M3
Torque	0.8 Nm
Rated cross section	4 mm <sup>2</sup>
Wire size (solid)	0.5 ... 6 mm <sup>2</sup>
Wire size (stranded)	0.5 ... 4 mm <sup>2</sup>
Rated voltage	380 V
Rated current	32 A
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-30°C ... 40°C
Photo	

**Data acc. to IEC 60947-7-1**

Flammability class acc. to UL94	V2
Pollution degree	3
Overvoltage category	III
Material group	II
Insulating material	PA 6.6
Stripping length	7 mm / earth connection terminal 10 mm

**Note**

Neutral (can be isolated): 1 screw connection, neutral isolation on busbar,  
 PE conductor: 1 screw connection, support rail  
 Phase conductor: 1 feed-through terminal with 2 screw connections



and 1 tapped hole for jumpers

