









## USB2.0 jack A/connector A (60 cm) RRJ\_USB

ront: USB2.0 jack type A rear: USB2.0 cable Description:

(length X=600 mm) with plug type A Attention: Mounting position of the USB jack does not comply with the USB2.0 specification

Category: Panel mount jacks RONTRON-R-JUWEL Series:

Ø 22.3 mm Panel cut-out: Degree of protection: IPOO \* 1) Illumination: no With labelling option:

Connection type: front: USB2.0 jack type A

no

rear: USB2.0 cable with connector type A

Front bezel silver-coloured -20°C ... 60°C Operating temperature: -25°C ... 80°C Storage temperature: 1,500 mating cycles Mechanical life:

Shape: round

Contact material: phosphor bronze, gold-plated 0.05 µm

## **Optional accessory**



Protective lid made of TPE AK22RRSW



Insulated plastic enclosure, 1 mounting hole DIRL1V-R22



Insulated plastic enclosure, 1 mounting hole DIRL1VGB-R22



Insulated plastic enclosure, 2 mounting holes DIRL2V-R22





Insulated plastic enclosure, 3 mounting holes DIRL3V-R22



Insulated plastic enclosure, 3 resp. 4 mounting holes DIRL4V-R22



Insulated plastic enclosure, 1 mounting hole IRL1M



Insulated plastic enclosure, 1 mounting hole IRL1M\_GELB



Insulated plastic enclosure, 2 mounting holes IRL2M



Insulated plastic enclosure, 3 mounting holes IRL3M



Insulated plastic enclosure, 5 mounting holes IRL5M



Protective lid, sealable KDP22RR





Robust protective lid, sealable KDPR22RR



Robust protective lid, sealable KDPR22RR\_SW



Adapter for panel mount jacks KRJM22R



LED light ring for status indication or additional illumination LR22K\_24B\_619



LED light ring for status indication or additional illumination LR22K\_24G\_619



RGB LED light ring for status indication or illumination LR22K\_24RGB\_619



LED light ring for status indication or additional illumination LR22K\_24R\_619



LED light ring for status indication or additional illumination LR22K\_24W\_619





LED light ring for status indication or additional illumination LR22K\_24Y\_619



Fixing nut for an extended clamping range up to 11 mm M22F



External nameplate holder RRJABT



Robust protection cap SDAL22RR



Robust protection cap SDVA22RR



Protection cap for hygienic applications SDVA22RRP



Insulated plastic enclosure with 1 mounting hole SIL22/1



High insulated plastic enclosure with 1 mounting hole SILH22/1

