



Key-operated switch, maintained, with 4-pole M12 connector SSSA12II_C009

| | |
|------------------------|--|
| Description: | with integrated 4-pole M12 connector, A coded including two keys other lock types on request |
| Category: | Key switches (momentary/maintained) |
| Series: | SHORTRON® connect |
| Panel cut-out: | Ø 22.3 mm |
| Mounting depth: | 33.7 mm |
| Protection class: | II (protective insulation) |
| Degree of protection: | IP65 (in the front); IP65 / IP67 (on the rear with plugged-in M12 connector) |
| Switching function: | maintained action |
| Travel: | 2.3 mm (pushbutton) |
| Illumination: | no |
| With labelling option: | no |
| Contact equipment: | 2 NO |
| Connection type: | 4-pole M12 connector (integrated), A coded |
| Front bezel: | silver-coloured |
| Operating temperature: | -25°C ... 70°C |
| Mechanical life: | 30,000 switching cycles |
| Electrical life: | 30,000 switching cycles at rated load |
| Storage temperature: | -40°C ... 80°C |
| Shape: | round |
| Contact material: | AgNi |

Optional accessory



Standard spare keys ESMIC482



Spacer ring SDR



Spacer ring SDRSW

Legend

I= Switching position >=

**Spring return O= Key
removable position**



Mounting bracket 135° / 1 mounting hole stainless steel
1.4301 S_CW145



Mounting bracket 90° / 1 mounting hole stainless steel 1.4301
S_CW190



Mounting bracket 135° / 2 mounting holes stainless steel
1.4301 S_CW245



Mounting bracket 90° / 2 mounting holes stainless steel 1.4301
S_CW290



Mounting bracket 135° / 3 mounting holes stainless steel
1.4301 S_CW345



Mounting bracket 90° / 3 mounting holes stainless steel 1.4301
S_CW390

