


Legend
I= Switching position >=
Spring return O= Key
removable position

**Key-operated switch, maintained, with 4-pole M12 connector
 SSSA14I_C007**

Description:	with integrated 4-pole M12 connector, A coded including two keys other lock types on request
Category:	Key switches (momentary/maintained)
Series:	SHORTRON® connect
Panel cut-out:	Ø 22.3 mm
Mounting depth:	33.7 mm
Protection class:	II (protective insulation)
Degree of protection:	IP65 (in the front); IP65 / IP67 (on the rear with plugged-in M12 connector)
Switching function:	maintained action
Travel:	2.3 mm (pushbutton)
Illumination:	no
With labelling option:	no
Contact equipment:	1 NO
Connection type:	4-pole M12 connector (integrated), A coded
Front bezel:	silver-coloured
Mechanical life:	30,000 switching cycles
Electrical life:	30,000 switching cycles at rated load
Storage temperature:	-40°C ... 80°C
Positive opening:	no
Operating temperature:	-25°C ... 70°C
Shape:	round
Contact material:	AgNi

Optional accessory

 Standard spare keys ESMIC482

 Spacer ring SDR

 Spacer ring SDRSW



Mounting bracket 135° / 1 mounting hole stainless steel
1.4301 S_CW145



Mounting bracket 90° / 1 mounting hole stainless steel 1.4301
S_CW190



Mounting bracket 135° / 2 mounting holes stainless steel
1.4301 S_CW245



Mounting bracket 90° / 2 mounting holes stainless steel 1.4301
S_CW290



Mounting bracket 135° / 3 mounting holes stainless steel
1.4301 S_CW345



Mounting bracket 90° / 3 mounting holes stainless steel 1.4301
S_CW390

