



|              |   |     |
|--------------|---|-----|
|              | L | R   |
| PIN 1/ PIN 2 |   |     |
| PIN 1/ PIN 4 |   |     |
| PIN 3 n.C.   | 0 | 1 2 |



### Key-operated switch, maintained, with 4-pole M12 connector SSWSSA17II\_C009

Description: with integrated 4-pole M12 connector, A coded including two keys other lock types on request

|                        |   |
|------------------------|---|
| Category:              | Key switches (momentary/maintained)   |
| Series:                | SHORTRON® connect   |
| Panel cut-out:         | Ø 22.3 mm   |
| Mounting depth:        | 33.7 mm   |
| Protection class:      | II (protective insulation)  |
| Degree of protection:  | IP65 (in the front);<br>IP65 / IP67 (on the rear with plugged-in M12 connector) |
| Switching function:    | maintained action   |
| Travel:                | 2.3 mm (pushbutton)   |
| Illumination:          | no  |
| With labelling option: | no  |
| Contact equipment:     | 2 NO  |
| Connection type:       | 4-pole M12 connector (integrated), A coded                                      |
| Front bezel            | black   |
| Mechanical life:       | 30,000 switching cycles   |
| Electrical life:       | 30,000 switching cycles at rated load   |
| Storage temperature:   | -40°C ... 80°C  |
| Positive opening:      | no  |
| Operating temperature: | -25°C ... 70°C  |
| Shape:                 | round   |
| Contact material:      | AgNi  |

### Optional accessory



Standard spare keys ESMIC482



Spacer ring SDR



Spacer ring SDRSW

Legend

I= Switching position >=

**Spring return O= Key  
removable position**



Mounting bracket 135° / 1 mounting hole stainless steel  
1.4301 S\_CW145



Mounting bracket 90° / 1 mounting hole stainless steel 1.4301  
S\_CW190



Mounting bracket 135° / 2 mounting holes stainless steel  
1.4301 S\_CW245



Mounting bracket 90° / 2 mounting holes stainless steel 1.4301  
S\_CW290



Mounting bracket 135° / 3 mounting holes stainless steel  
1.4301 S\_CW345



Mounting bracket 90° / 3 mounting holes stainless steel 1.4301  
S\_CW390

