



0 1 2

PIN 1 / PIN 2



### Illuminated pushbutton with 4-pole M12 connector SSWTLI\_C005

|                        |   |
|------------------------|---|
| Description:           | with integrated 4-pole M12 connector, A coded incl. white LED |
| Category:              | Pushbuttons   |
| Series:                | SHORTRON® connect   |
| Panel cut-out:         | Ø 22.3 mm   |
| Mounting depth:        | 33.7 mm   |
| Protection class:      | II (protective insulation)                                    |
| Degree of protection:  | IP65 / IP67   |
| Switching function:    | momentary action  |
| Travel:                | 2.3 mm (pushbutton)   |
| Illumination:          | yes   |
| With labelling option: | yes   |
| Contact equipment:     | 1 NO  |
| Connection type:       | 4-pole M12 connector (integrated), A coded                    |
| Front bezel            | black   |
| Positive opening:      |   |
| Operating temperature: | -25°C ... 70°C  |
| Mechanical life:       | 1 million switching cycles                                    |
| Electrical life:       | 1 million switching cycles                                    |
| Storage temperature:   | -40°C ... 80°C  |
| Shape:                 | round   |
| Contact material:      | AgNi  |
| Lamp socket:           | none, with integrated 3 mm LED white                          |

### Optional accessory



Protective lid made of TPE AK22RRSW



Robust protective lid, sealable KDPR22RR



Robust protective lid, sealable KDPR22RR\_SW



Spacer ring SDR



Spacer ring SDRSW



Mounting bracket 135° / 1 mounting hole stainless steel  
1.4301 S\_CW145



Mounting bracket 90° / 1 mounting hole stainless steel 1.4301  
S\_CW190



Mounting bracket 135° / 2 mounting holes stainless steel  
1.4301 S\_CW245



Mounting bracket 90° / 2 mounting holes stainless steel 1.4301  
S\_CW290



Mounting bracket 135° / 3 mounting holes stainless steel  
1.4301 S\_CW345



Mounting bracket 90° / 3 mounting holes stainless steel 1.4301  
S\_CW390



Sealing cap TK28S

