



Pushbutton with 4-pole M12 connector SVATOI_C008

Category:	Pushbuttons
Series:	SHORTRON® connect
Panel cut-out:	Ø 22.3 mm
Mounting depth:	33.7 mm
Protection class:	II (protective insulation)
Degree of protection:	IP65 / IP67 (in the front); IP65 / IP67 (on the rear with plugged-in M12 connector)
Switching function:	momentary action
Travel:	2.3 mm
Illumination:	no
With labelling option:	yes
Contact equipment:	1 NC + 1 NO
Connection type:	4-pole M12, A coded
Front bezel:	stainless steel, polished
Mechanical life:	1 million switching cycles
Electrical life:	1 million switching cycles; DC13: max. 100,000
Shape:	round

Optional accessory



Spacer ring SDR



Spacer ring SDRSW



Mounting bracket 135° / 1 mounting hole stainless steel
1.4301 S_CW145



Mounting bracket 90° / 1 mounting hole stainless steel 1.4301
S_CW190



Mounting bracket 135° / 2 mounting holes stainless steel
1.4301 S_CW245



Mounting bracket 90° / 2 mounting holes stainless steel 1.4301
S_CW290



Mounting bracket 135° / 3 mounting holes stainless steel
1.4301 S_CW345



Mounting bracket 90° / 3 mounting holes stainless steel 1.4301
S_CW390



Sealing cap TK28S

