



Legend  
**I= Switching position >=**

### Illuminated selector switch, maintained, with 4-pole M12 connector SVAWALI\_C005

Description:	with integrated 4-pole M12 connector, A coded incl. white LED
Category:	Selector switches (momentary/maintained)
Series:	SHORTRON® connect
Panel cut-out:	Ø 22.3 mm
Mounting depth:	33.7 mm
Protection class:	II (protective insulation)
Degree of protection:	IP65 (in the front); IP65 / IP67 (on the rear with plugged-in M12 connector)
Switching function:	maintained action
Travel:	2.3 mm (pushbutton)
Illumination:	yes
With labelling option:	no
Contact equipment:	1 NO
Connection type:	4-pole M12 connector (integrated), A coded
Front bezel:	stainless steel, polished
Positive opening:	
Operating temperature:	-25°C ... 70°C
Mechanical life:	30,000 switching cycles
Electrical life:	30,000 switching cycles at rated load
Storage temperature:	-40°C ... 80°C
Shape:	round
Contact material:	AgNi
Lamp socket:	none, with integrated 3 mm LED white

### Optional accessory



Spacer ring SDR



Spacer ring SDRSW



Mounting bracket 135° / 1 mounting hole stainless steel  
 1.4301 S\_CW145

**Spring return**



Mounting bracket 90° / 1 mounting hole stainless steel 1.4301  
S\_CW190



Mounting bracket 135° / 2 mounting holes stainless steel  
1.4301 S\_CW245



Mounting bracket 90° / 2 mounting holes stainless steel 1.4301  
S\_CW290



Mounting bracket 135° / 3 mounting holes stainless steel  
1.4301 S\_CW345



Mounting bracket 90° / 3 mounting holes stainless steel 1.4301  
S\_CW390

