

FRVKALOOI

17.03.2022

**Emergency-stop made of aluminium
for robust applications**



General Data

Type reference	FRVKALOOI
Description	Emergency-stop head, aluminium version, foolproof
Approvals	CCC, CE, cURus, TÜV_Süd, UKCA
Contact type	2 NC + 1 NO
Degree of protection	IP65 / IP67
Connection type	Faston terminals 2.8 x 0.8 mm
Contact material	AgNi
Max. storage temperature	-40°C ... 80°C
Max. operating temperature	-25°C ... 70°C
Mechanical life	50,000 switching cycles
Electrical life (rated load)	50,000 switching cycles at rated load
Contact resistance NO	< 20 mOhm
Contact resistance NC	< 20 mOhm
Bouncing time NO	< 10ms
Bouncing time NC	< 10ms
Positive opening contact	acc. to EN60947-5-1, appendix K

Electrical data acc. to IEC/EN 60947-5-1 (VDE 0660 Sect. 200)

	alternate current	direct current
Utilisation category	AC15 B300	DC13 Q300
Rated insulation voltage Ui	250 V	250 V
Rated operating voltage Ue	240 V / 120 V	250 V / 125 V / 60 V / 24 V
Rated operating current Ie	1.5 A / 3 A	0.27 A / 0.55 A / 1 A / 2 A
Breaking capacity	10Ie	1,1Ie
Continuous thermal current	5 A	-

Additional data

Mounting aperture	22.3 mm
-------------------	---------



Tightening torque (mounting nut)	1.3 ... 1.9 Nm
Release	twist release, left or right
Mounting position	any
Standards	EN 60947-5-1, EN 60947-5-5, EN ISO 13850
Ld	20% (NC)
B10d [cycles]	250,000
Overvoltage category	II
Rated impulse voltage	2.5 kV
Pollution degree	2

Note

O = NC contact; I = NO contact
with switching position indicator

Data acc. to UL

Rating contact block	B300, 24 V dc/3 A
NEMA TYPE	4x indoor (front face)
Torque	1.3 ... 1.9 Nm (head nut)

