

Emergency-stop FRVKOOP

Category:	Emergency-stops
Series:	SHORTRON®
Panel cut-out:	Ø 22.3 mm
Mounting depth:	9 mm
Degree of protection:	IP65 / IP67
With labelling option:	no
Contact equipment:	2 NC
Connection type:	PCB-mount terminals
Front bezel	yellow
mushroom head	red
Shape:	round
Foolproof:	yes
Anti-lock collar:	no
Switching position	yes
indicator:	
Release:	twist right or left
Contact material:	AgNi

Optional accessory



Insulated plastic enclosure, 1 mounting hole DIRL1V-R22



Insulated plastic enclosure, 1 mounting hole DIRL1VGB-R22



Insulated plastic enclosure, 2 mounting holes DIRL2V-R22



Insulated plastic enclosure, 3 mounting holes DIRL3V-R22




Insulated plastic enclosure, 3 resp. 4 mounting holes DIRL4V-R22



Insulated plastic enclosure, 1 mounting hole IRL1M



Insulated plastic enclosure, 1 mounting hole IRL1M_GELB



Insulated plastic enclosure, 2 mounting holes IRL2M



Insulated plastic enclosure, 3 mounting holes IRL3M



Insulated plastic enclosure, 5 mounting holes IRL5M



Yellow nameplate NAS_22



Yellow nameplate with quadrilingual imprint NAS_22_548



Protective shroud RRSK



Insulated plastic enclosure with 1 mounting hole SIL22/1



High insulated plastic enclosure with 1 mounting hole SILH22/1

