

## Emergency-stop 2NC FRVKOO

Category:	Emergency-stops
Series:	SHORTRON®
Panel cut-out:	Ø 22.3 mm
Mounting depth:	18,1 mm
Degree of protection:	IP65 / IP67
Illumination:	no
With labelling option:	no
Contact equipment:	2 NC
Connection type:	Faston terminals 2.8 x 0.8 mm
Front bezel	yellow
mushroom head	red
Mechanical life:	50,000 switching cycles
Shape:	round
Electrical life:	50,000 switching cycles at rated load
Storage temperature:	-40°C ... 80°C
Positive opening:	acc. to EN60947-5-1, appendix K
Operating temperature:	-25°C ... 70°C
Foolproof:	yes
Anti-lock collar:	no
Switching position indicator:	yes
Release:	twist right or left
Contact material:	AgNi

## Optional accessory



Insulated plastic enclosure, 1 mounting hole DIRL1V-R22



Insulated plastic enclosure, 1 mounting hole DIRL1VGB-R22



Insulated plastic enclosure, 2 mounting holes DIRL2V-R22



Insulated plastic enclosure, 3 mounting holes D1RL3V-R22



Insulated plastic enclosure, 3 resp. 4 mounting holes D1RL4V-R22



Faston clamp 2.8 x 0.8 mm with snap-in pin FH2,8




Insulating case IH2,8



Insulated plastic enclosure, 1 mounting hole IRL1M




Insulated plastic enclosure, 1 mounting hole IRL1M\_GELB



Insulated plastic enclosure, 2 mounting holes IRL2M



Insulated plastic enclosure, 3 mounting holes IRL3M



Insulated plastic enclosure, 5 mounting holes IRL5M

Yellow nameplate NAS\_22



Yellow nameplate with quadrilingual imprint NAS\_22\_548



Protective shroud RRSK



Insulated plastic enclosure with 1 mounting hole SIL22/1



High insulated plastic enclosure with 1 mounting hole SILH22/1

