



## Emergency-stop head RKUV28

Description:	with snap-action mechanism
Category:	Setas de emergencia
Series:	OKTRON®-R
Panel cut-out:	Ø 16.2 mm
Degree of protection:	IP65 / IP67 / IP69K
Travel:	3 mm
Illumination:	no
With labelling option:	no
Front bezel	yellow
mushroom head	red
Operating temperature:	-30°C ... 70°C
Mechanical life:	30,000 switching cycles
Shape:	round
Permissive contact:	no
Storage temperature:	-50°C ... 85°C
Foolproof:	si
Anti-lock collar:	no
Switching position indicator:	si
Release:	twist right or left

## Optional accessory



ASI\_SAW16A



ASI\_SAW16E



AZ2N



AZ40



AZOSOI



AZOSOI\_AU



AZSOSO



AZSOSO\_AU



BZO



BZOI



BZOIK



BZOIK\_AU



BZOI\_AU



BZOK



BZOO



BZOOK



BZOOK\_AU



BZOO\_AU



BZO\_AU



DIRL1V-R16



DIRL1VGB-R16



DIRL2V-R16



DIRL3V-R16



DIRL4V-R16



FRTOI\_C008



FRTOI\_C118



FRTOOI\_C112



FRTOO\_C001



FRTOO\_C111



FRTO\_C006



FRTO\_C116



NAS\_16



NAS\_16\_548



RKSK



SIL16/1



SILH16/1

