



Emergency-stop head RKUV40

Category:	Setas de emergencia
Series:	OKTRON®-R
Panel cut-out:	Ø 16.2 mm
Degree of protection:	IP65 / IP67
Travel:	3 mm
Illumination:	no
With labelling option:	no
Front bezel	yellow
mushroom head	red
Permissive contact:	no
Storage temperature:	-50°C ... 85°C
Operating temperature:	-30°C ... 70°C
Mechanical life:	30,000 switching cycles
Shape:	round
Foolproof:	si
Switching position indicator:	no
Anti-lock collar:	si
Release:	twist right or left

Optional accessory



AZ2N



AZ4O



AZOSOI



AZOSOI_AU



AZSOSO



AZSOSO_AU



BZO



BZOI



BZOIK



BZOIK_AU



BZOI_AU



BZOK



BZOO



BZOOK



BZOOK_AU



BZOO_AU



BZO_AU



DIRL1V-R16



DIRL1VGB-R16



DIRL2V-R16



DIRL3V-R16



DIRL4V-R16



FRTOI_C008



FRTOI_C118



FRTOOI_C112



FRTOO_C001



FRTOO_C111



FRTO_C006



FRTO_C116



NAS_16



NAS_16_548



SIL16/1



SILH16/1

