



Legend  
**I= Switching position >=**  
**Spring return O= Key**  
**removable position**

**Key actuator, maintained (3 different keys) OKSSA31**

Description:	including 3 keys: 1st key: two-way operation 2nd key: operation to the left only 3rd key: operation to the right only
Category:	Key switches (momentary/maintained)
Series:	OKTRON®
Panel cut-out:	Ø 16.2 mm
Protection class:	II (aislamiento protector)
Degree of protection:	IP65
Switching function:	maintained action
Travel:	
Illumination:	no
With labelling option:	no
Front bezel	charcoal
Storage temperature:	-50°C ... 85°C
Operating temperature:	-25°C ... 70°C
Mechanical life:	The mechanical life time depends on the type and number of contact blocks being used.
Shape:	square

**Optional accessory**



ASI\_BZ



AZ2N



AZ4I



AZ40



BZII



BZIIK



BZIIK\_AU



BZII\_AU



BZOI



BZOIK



BZOIK\_AU



BZOI\_AU



BZOO



BZOOK



BZOOK\_AU



BZOO\_AU



BZ\_439



BZ\_439\_AU



BZ\_494



CT2



CT2\_549



CZTP2\_549



Dirl1V-R16



Dirl1VGB-R16



Dirl2V-R16



Dirl3V-R16



Dirl4V-R16



ESMIC482



FRTIL\_C119



FRTOI\_C118



FRTOO\_C111



QXABT



QXABT\_M



SIL16/1



SILH16/1

