



Legend
I= Switching position >=
Spring return O= Key
removable position

Key actuator, maintained OKSSMA12

Description:	including two keys other lock types on request
Category:	Key switches (momentary/maintained)
Series:	OKTRON®
Panel cut-out:	Ø 16.2 mm
Protection class:	II (aislamiento protector)
Degree of protection:	IP65
Switching function:	maintained action
Travel:	
Illumination:	no
With labelling option:	no
Front bezel	silver-coloured
Positive opening:	no
Storage temperature:	-50°C ... 85°C
Operating temperature:	-25°C ... 70°C
Mechanical life:	The mechanical life time depends on the type and number of contact blocks being used.
Shape:	square

Optional accessory



ASI_BZ



AZ2N



AZ4I



AZ4O



BZII



BZIIK



BZIIK_AU



BZII_AU



BZOI



BZOIK



BZOIK_AU



BZOI_AU



BZ00



BZ00K



BZ00K_AU



BZ00_AU



BZ_439



BZ_439_AU



BZ_494



CT2



CT2_549



CZTP2_549



DIRL1V-R16



DIRL1VGB-R16



DIRL2V-R16



DIRL3V-R16



DIRL4V-R16



ESMIC482



FRTIL_C009



FRTIL_C119



FRTOI_C008



FRTOI_C118



FRTOO_C001



FRTOO_C111



QXABT



QXABT_M



SIL16/1



SILH16/1

