



Legend
I= Switching position >=
Spring return O= Key
removable position

Key actuator, maintained (3 different keys) OKSSMA31

Description: including 3 keys: 1st key: two-way operation 2nd key: operation to the left only 3rd key: operation to the right only

Category: Key switches (momentary/maintained)
 Series: OKTRON®
 Panel cut-out: Ø 16.2 mm
 Protection class: II (aislamiento protector)
 Degree of protection: IP65
 Switching function: maintained action
 Travel: no
 Illumination: no
 With labelling option: no
 Front bezel: silver-coloured
 Positive opening: no
 Storage temperature: -50°C ... 85°C
 Operating temperature: -25°C ... 70°C
 Mechanical life: The mechanical life time depends on the type and number of contact blocks being used.
 Shape: square

Optional accessory



ASI_BZ



AZ2N



AZ4I



AZ40



BZII



BZIIK



BZIIK_AU



BZII_AU



BZOI



BZOIK



BZOIK_AU



BZOI_AU



BZOO



BZOOK



BZOOK_AU



BZOO_AU



BZ_439



BZ_439_AU



BZ_494



CT2



CT2_549



CZTP2_549



Dirl1V-R16



Dirl1VGB-R16



Dirl2V-R16



Dirl3V-R16



Dirl4V-R16



ESMIC482



FRTIL_C119



FRTOI_C118



FRTOO_C111



QXABT



QXABT_M



SIL16/1



SILH16/1

